



Changing the Paradigm of Air Pollution Monitoring....Opportunities and Challenges

Presented by David Shelow (EPA OAQPS)

Emily Snyder, Tim Watkins, Eben Thoma, Gayle Hagler, Ron Williams – EPA ORD, and variety of other contributors.



A technology shift is under way......

Technology advances are supporting a shift toward new ways of measuring and communicating air quality information


Smartphone / tablet generation

e.g., fitbit activity tracker



- Miniaturization of sensors
- Lower-cost components








- Easy to use
- Crowd-funding supporting DIY innovation




And a cultural shift is under way

Where we are today: governmentprovided data, AQI on broad time and spatial scales Public demand for more personalized information – what about *my* exposure, *my* neighborhood, *my* child??






Imagine a different air monitoring landscape...




Neighborhood next to industry......






Open-path instruments



Seeing invisible VOC leaks with infrared video FLIR Camera





Off-site assessment with GMAP-REQ

(Geospatial Measurement of Air Pollution – Remote Emissions Quantification)

wind direction




- Position vehicle in the plume
- Acquire methane (CH₄), H2S and wind data for 20 minutes
- Pull a canister sample for volatile organic compound (VOC) information


driving path




Spike in CH₄ indicates emission



Low cost sensors can provide industry 24-7 observation







Fixed location sensors examples



Aqmesh.com: AQ electrochemical sensors



Fixed location sensors examples




Fixed Sensor Specifications

SENSOR *	RANGE (@0°C I ATM)	PRECISION	LOW DETECTION LIMIT	RESOLUTION	BACKGROUND NOISE	ACCURACY	RESPONSE (T90)
CARBON MONOXIDE (CO)	0-100 mg/m³ 0-80 ppm	< 2% f.s.	0.1 mg/m3	0.1 mg/m ³	0.1 % f.s.	+/- 0.5 mg/m ³	< 3 sec.
NITROGEN DIOXIDE (NO ₂)	0-500 μg/m³ 0-400 ppb	< 2% f.s.	0.1 μg/m3	0.1 μg/m³	0.1 % f.s.	+/- 10 µg/m³	< 3 sec.
OZONE (O ₃):	20-500 μg/m³ 10-200 ppb	< 10% f.s.	20 μg/m3	1.0 µg/m³	0.1 % f.s.	+/- 10 µg/m³	< 3 sec.
BENZENE (C,H,)	0-100 μg/m³ 0-30 ppb	< 2% f.s.	0.1 μg/m3	0.1 µg/m³	0.1 % f.s.	+/- μg/m³	< 3 sec.
NITROGEN OXIDES (NOX)	0-800 µg/m3 0-500 ppb	< 2% f.s.	0.1 µg/m3	0.1 µg/m3	0.1 % f.s.	+/- 10 µg/m3	< 3 sec. 0
METHANE (CH₄)	0-300 μg/m³ 0-400 ppb	< 2% f.s.	0.1 μg/m3	l μg/m³	0.1 % f.s.	+/- 10 µg/m³	< 3 sec.
OPERATIVE CONDITIONS	Temperature: -20°C to 50°C Relative Humidity: 5 to 95% (non condensating) ZERO/SPAN DRIFT			< 2.5% / 6 months < 2.5% / 3 months (for O ₃)			
Unil		VIA	TEC srI C. COLOMBO, 3 00 FERRARA (ITA		EL. +39 0532.731123 AX +39 0532.730537		v.unitec-srl.co @unitec-srl.co
							nown Zone



Village Green Project design



Let's take it another step forward...citizen monitoring/crowdsourcing





Michael Heimbinder, Habitat Map, Brooklyn NY




Share Your Air!

Michael Heimbinder, Habitat Map, Brooklyn NY









M-Pod Components

Mike Hannigan - Univ. of Colorado



Sensor	Gas Measured	Technology		
e2v, MICS-2614	Ozone	Metal Oxide Semiconductor		
ELT, S100	Carbon Dioxide	Non-Dispersive Infrared		
e2v, MICS-5526	Carbon Monoxide, and VOC	Metal Oxide Semiconductor		
e2v, MICS-4514	Carbon Monoxide, VOC, and Nitrogen Dioxide	Metal Oxide Semiconductor		
Sensirion, SHT21	Temperature, and Humidity	Digital Humidity and Temperature Sensors		

How big is it?



<u>Some Specs:</u> Lifetime on a charge = 10 - 18 hrs Cost to construct = \$350

Wearable Monitors



Wear Air (CMU): VOC sensor

Let's take it even further...personal monitoring

What if we can monitor our health response to air pollution......

Advanced Self-Powered Systems of Integrated Sensors and Technologies

Veena Misra

North Carolina State University























Health response



Exposure tracking



Application	Body	Environment
Asthma	EKG,EEG, EMG, wheezing, Pulse Ox, Skin- cond, cortisol	NO ₂ , CO, Ozone, VOCs,
Heart Disease		Particulates Noise Heat Stress Light Stress

Long-term monitoring of selected environmental and health parameters

Impact:

- Exposure Sciences
- Chronic Disease
- Health care costs and policy

Courtesy of Veena Misra

Other wearable devices.....



Conscious Clothing – measuring breathing rates/volume and heart rates





Challenges

- Data Quality
- Sensors for Air Toxics vs Criteria Pollutants
- Levels of detection
 - Fenceline vs Ambient concentrations
- Large data sets
- Health Messaging what does the data mean?
- Acute Rfc (Inhalation Reference []) values
 - Chronic vs Acute

How can we, EPA, help?

- EPA Hosted NGAM Workshops
- Work with sensor manufacturers
- Community Tool box
 - Acute Rfc values communication
- Sensor Evaluation studies
 - Chamber studies
 - Pilot studies with FRM/FEM's
- Information Clearinghouse websites





In Summary

- Supplement regulatory monitoring programs
- Empower communities
- Enhance source compliance monitoring
- Personal exposures and response monitoring
- A cultural and technological shift is coming and we need to help guide it to become the next generation air monitoring.

Disclaimer

 The contents do not reflect the views or policies of the Agency. The engineering and equipment descriptions contained here are illustrative and mention of trade names or commercial products do not constitute endorsement or recommendation for use.

Websites

- http://www.epa.gov/research/airscience/next
 -generation-air-measuring.htm
- http://www.citizenair.net
- http://communitysensing.org
- http://aircasting.org
- http://citizensensor.cc