

Some results of EPA Research on Permeable Pavement

Michael Borst

Engineer

U.S. Environmental Protection Agency

Edison, NJ

*Site visit from NYC DDC, NYC DOT, and HD Inc.
August 7, 2017*

Discussion with municipal and state decision makers emphasized two research needs often lacking in existing data.

- Real-world scale
- Long-term monitoring



EPA has ongoing permeable pavement research at three locations

- Edison, NJ
- Louisville, KY
- Fort Riley, KS



EDISON, NJ

To get measurements at the real-world scale, we need to be involved in the design stage.



In 2009, EPA designed and built a 1-acre parking lot for facility staff and visitors that was surfaced with three types of permeable pavement.



EPA Facility Parking Lot
Edison, New Jersey

Overall, construction took about a year.

November 26, 2008



February 26, 2009



March 25, 2009



June 1, 2009



October 6, 2009




October 8, 2009

August 5, 2009



October 28, 2009

The design incorporated water quality and hydrologic monitoring capabilities.



- | | | | |
|------------------------------|-------------------|-----------------|--------------|
| Interlocking concrete pavers | Pervious concrete | Porous asphalt | Rain gardens |
| Buried distribution pipes | Tree islands | Hot mix asphalt | |
| Buried well/piezometers | Collection tanks | Buried WCRs | |



Interlocking concrete paver installation took a little more than a week.



The porous concrete pour took two days followed by a week of covered cure time



Placing the porous asphalt took two days.



Vertical cross sections of permeable sections varied slightly from material to material.



**Concrete Pavers
(3.125 in.)**


**AASHTO No. 8
(2 in.)**

**AASHTO No. 57
(4 in.)**

**AASHTO No. 2
RCA (depth varies)**

EPDM Membrane

Existing Subgrade



**Pervious Concrete
(6 in.)**

**AASHTO No. 2
RCA (depth varies)**

EPDM Membrane

Existing Subgrade



Not to scale

**Porous Asphalt
(3 in.)**


**AASHTO No. 2
RCA (depth varies)**

EPDM Membrane

Existing Subgrade

Based on engineering drawings from Morris & Ritchie Associates, Inc. 2009

Post excavation testing showed large infiltration rates for the underlying soil.



Four equally-sized and spaced lined sections collect infiltrating water from each monitored permeable surface with the balance infiltrating to the underlying soil.



Infiltrate drains from the lined sections to 1,500-gallon tanks on the east side of the parking lot where it can be sampled.




The tanks are designed to collect a 1.5-inch rain event before bypassing.




**We manage snow and ice with calcium chloride
(with no sand) and a rubber edged plow blade.**




After winter salt application, chloride concentration decreases throughout the remainder of the year.



All permeable surfaces reduced Suspended Solids Concentration (SSC) to different degrees.



Acidic rainfall is buffered by all pavement surfaces, but the pH of the PA exfiltrate is surprisingly high.



SURFACE INFILTRATION & SURFACE CLOGGING


We measured surface infiltration rates using a modified version of ASTM C1701 at roughly monthly intervals for about three years.



Modifications were

- (1) how the seal was achieved between the ring and the surface
- (2) added temperature measurements of surface and water.

We monitored the four permeable sections.




- | | | | |
|------------------------------|-------------------|-----------------|--------------|
| Interlocking concrete pavers | Pervious concrete | Porous asphalt | Rain gardens |
| Buried distribution pipes | Tree islands | Hot mix asphalt | |
| Buried well/piezometers | Collection tanks | Buried WCRs | |


The infiltration rate varies among the four tested surfaces, but all surfaces are sufficient to handle maximum expected direct rainfall rates.

**100-year, 5-minute
rainfall intensity**

- Edison, NJ
20.8 cm/hr (8.2 in/hr)




Infiltration decreased with age for the three surfaces that received run-on from driving lane.




Bars represent standard error.

We developed a working hypothesis of the mechanics of the infiltration processes.




As gaps fill with sediment, the location of the primary infiltration area moved downgradient.



Large response

Medium response

Inspection supports the proposed mechanism.




The progressive accumulation was also visible in the PICP section.



No sediment

Sediment


The surface clogging progression has varied slightly because of microtopography.






LOUISVILLE, KY


We expect flow to concentrate along the curb with much smaller flows from the road crown and direct rainfall entering elsewhere.



We expect the concentrated flow to transport and deposit sediment from the drainage area.



Time Domain Reflectometers (TDRs) were installed 40 cm below the paver surface in the aggregate to measure surface clogging progression.




The foundational research¹ linking the TDR response to moisture content was done in mineral soils, not gravel so the output value is the “Relative Volumetric Water Content” (RVWC).




1 Topp, G. C., Davis, J. L., and Annan, A. P. (1980). “Electromagnetic determination of soil water content: Measurements in coaxial transmission lines.” *Water Resources Research*, 16, 574-582.


Using the TDRs nearest the curb edge, we can monitor the progression of surface clogging.



The curb edge TDR responses support the predicted clogging progression.



The TDR response can be used to determine the control's longitudinal clogging rate as a function of rainfall.




Control Louisville 19G


Response threshold 0.10 RVWC

The initial clogging rate was about 0.123 m per mm (10 ft per inch) of rain.

Infiltration tests and field visits were used to support the threshold selection.



Visual inspection on February 1, 2012 confirmed where a surface was clogged.



Control 19G
Length: 12.2 m




Control 19G
Length: 22.9 m

Photo: Josh Rivard
University of Louisville

Street slopes (longitudinal and transverse) and curbs (height and condition) are important considerations when placing the controls in a curb and gutter system.

Curb / Sidewalk



Crown of road

Short curbs by design (or resulting from multiple resurfacing without milling) will limit the working flow width of the control.


Steeper slopes concentrate flow and use less surface area.



The important consideration is working surface area, not surface area.


It is not obvious what to use as a working width (e.g., mean / median calculated 5-minute average flow width).

The current ICPI guidance is a ratio of control area to drainage area.



50% of 5-minute average flow widths
(excluding infiltration) are 0.75 ft or less


If this model is accurate, the particle size distribution of up gradient and down gradient sediment should differ.




Large response

Medium response

Particle size distribution of the clogging sediment collected from a control in Louisville.



- 19 G-A
- ◆ 19 G-B
- ▲ 19 G-C
- 19 G-D



Removing pavers at selected locations shows how clogging advances with gaps filled and small debris loading.



With aggregate between the pavers, most of the fines are trapped in the top 20 mm.



When pavers are installed without interstitial gravel, sediment progresses the full depth of the paver.



OTHER STUFF

As part of the research in Louisville we looked at three maintenance techniques.



(a)




(b)



(c)

Intra-event exfiltration can be significant part of the collected water volume for long duration events



Level data at 1-minute intervals

Rainfall data from MSD gauge TR05 at 5-minute intervals

Large portions of the pervious concrete at the Edison site disaggregated.



The problem first became apparent about 18 months after pouring concrete. It was repaired by the contractor in May 2011, but has recurred.



The raveling did not penetrate the full depth of the porous concrete.



Is structural failure coupled with chloride?



April 14, 2014

WYOMING ANALYTICAL LABORATORIES, INC.
(303) 278-3446
Fax: (303) 278-3439
www.wal-lab.com
Email: wlabray@aol.com

May 06, 2014

140403

Customer ID: 119176 Permeable Concrete
1 119176 Permeable Concrete Core Sample "EPA" 0-2"
2 119176 Permeable Concrete Core Sample "EPA" 3-4"
3 119176 Permeable Concrete Core Sample "EPA" 5-6"
4 119177 Permeable Concrete Sample "Trump F" Sample A
5 119177 Permeable Concrete Sample "Trump F" Sample B

Water Soluble Mg: 0.017


Wt. %, as Received Basis: <0.001, 0.006, 0.051, 0.149

Analysis in Accordance with ASTM C-1218 and X-Ray Fluorescence Spectrometry (XRF)

Charles R. Wilson
Division Manager

MEMBER
ACIL

Page 1 of 1



NRMCA revised O&M guidance (2015)

“Deicing chemicals should not be used on any type of concrete in the first year.”





Michael Borst

borst.mike@epa.gov