

# Manganese Treatment and Distribution System Management

Asher Keithley, PhD, PE

Darren Lytle, PhD, PE


U.S. EPA, Office of Research and Development

# Mn Occurrence and Regulatory Status

## Groundwater



## Surface Water




Arnold et al. (2021)

- Included in Unregulated Contaminant Monitoring Rule (UCMR) 4
  - Maps show maximum entry point concentration from UCMR 4 (2017-2021)
- Included on Contaminant Candidate List (CCL) 5
- Health Advisory Levels (HALs)
  - 0.3 mg/L for lifetime and infant acute
  - 1 mg/L for acute
- Secondary Maximum Contaminant Level (SMCL) = 0.05 mg/L

# Biological Treatment of Groundwaters

- Reducing conditions (low dissolved oxygen) with multiple contaminants
  - Ammonia, iron, arsenic, manganese, methane
- Aerated contactor + filter bioreactor
  - Continuous air sparging satisfies  $O_2$  demand for nitrification  $\sim 4.6 \text{ mg } O_2 / \text{mg } NH_3\text{-N}$
  - Most oxidation occurs in contactor
  - Filter provides particle removal and additional oxidation




# Pilot- and Full-Scale Small System in Iowa


- Pilot study August 2016 – July 2017

Parameter	Well
Arsenic	27 $\mu\text{g/L}$
Iron	4.25 mg/L
Manganese	0.16 mg/L
Ammonia	3.0 mg N/L
TOC	3.0 mg/L
pH	7.55
Hardness	332 mg/L $\text{CaCO}_3$
Alkalinity	410 mg/L $\text{CaCO}_3$


A




B



C



D



# Pilot- and Full-Scale Treatment at a Small System in Iowa

## Full Scale Design


Parameter	Units	Value
Plant capacity	gpm	400
Average day flow	gpm	180
Number of contactors	--	2
Contactor diameter	ft	11
Contactor bed depth	ft	4.58
Contactor media type	--	Gravel
Contactor avg loading rate	gpm/ft <sup>2</sup>	0.95
Contactor avg EBCT	min	36
Number of filters	--	4
Filter media type	--	Anthracite/ Sand

## Start Up Schedule


Date	Notes
November 2020	Started flow through contactors
February 2021	EPA-ORD sampling program started
February 2021	Started flow through filters
April 2021	Decreased PO <sub>4</sub> feed to improve arsenic removal
July 2021	Online and operating at full capacity
January 2022	EPA-ORD sampling program ended

# Pilot- and Full-Scale Treatment at a Small System in Iowa

Incomplete nitrification in contactors




Typically complete nitrification in filters






# Pilot- and Full-Scale Treatment at a Small System in Iowa

Avg filter effluent Mn = 5  $\mu\text{g/L}$



Avg filter effluent As = 5.8  $\mu\text{g/L}$



**Key takeaway:** Aerated contactor + filter biotreatment system effectively treated arsenic, iron, manganese, and ammonia

# Mn Removal within Aerated Contactor

- Where does Mn removal occur within aerated contactors?
  - Different mixing and DO profiles than filters
- What is the relationship between media surface Mn and Mn oxidases concentrations?
- Collected media samples at influent end, middle, and effluent end of 6 pilot-scale aerated contactors

Parameter	Range
NH <sub>3</sub>	2.3 - 3.4 mg N/L
Fe	0.1 - 3.95 mg/L
Mn	2 - 196 µg/L
As	< 4 - 23 µg/L
TOC	0.1 - 7.1 mg/L
pH	6.5 - 7.9
Hardness	215 - 374 mg/L CaCO <sub>3</sub>


Parameter	Range
Media Type	Ceramic, GAC, Gravel
Loading Rate	3.1-7.3 m/h
EBCT	9-25 min
Air:Water Ratio	6-11 L/min:L/min






● 1b ● 2 ● 3 ● 4 ● 5

Contactor Depth



Mn oxidases by Contactor and Influent Mn conc.

● 1a ● 1b ● 2 ● 3 ● 4 ● 5



# Distribution System Mn after Switching Sources


- System had been operating with  $\text{Mn} > 2 \text{ mg/L}$  for decades
- Recently switched sources to a source with low Mn
  - Otherwise similar water quality
- Chloramines for disinfectant residual
- Dose blended  $\text{PO}_4$ . Plan to slowly convert to ortho- $\text{PO}_4$  after system acclimates to new source
- Monthly sampling at entry point + 9 sites in the distribution system
  - 4 events before the switch
  - 3 events since the switch

# Water Quality – Entry Point

Parameter	Before Switch	After Switch
pH	7.60	8.30
Mn (mg/L)	2.29	0.021
Fe (mg/L)	0.122	0.012
Ca (mg/L)	72.7	55.7
Mg (mg/L)	28.6	26.0
Total Cl2 (mg/L)	1.30	2.29




● Total    ▲ Particulate    ■ Colloidal    — Dissolved  
                 > 0.2 μm    30 kDa - 0.2 μm    < 30 kDa




# Mn Speciation

- Particulate > 0.2  $\mu\text{m}$
- Colloidal 30 kDa-0.2  $\mu\text{m}$
- Dissolved < 30 kDa



# Summary

- Manganese is prevalent in regions throughout the U.S.
  - A Mn regulation could necessitate systems to install treatment and manage legacy Mn in the distribution system
  - Biological treatment of groundwaters with multiple contaminants via aerated contactor + filter consistently achieved  $\text{Mn} < 10 \mu\text{g/L}$
  - Mn surface concentrations greatest at influent end of contactor and not related to Mn oxidases concentrations
  - Total Mn decreased substantially after switching sources, but evidence of some instability in Mn particulates farther out in DS
- 



## ***Acknowledgements***

- EPA: Matt Noerpel
- Water systems operators
- WesTech: Eric Lawrence, Tom Dumbaugh

## ***Questions?***


Asher Keithley, PhD, PE  
keithley.asher@epa.gov  
513-569-7269

## ***Notice***

*The U.S. Environmental Protection Agency, through its Office of Research and Development, funded and managed, or partially funded and collaborated in, the research described herein. It has been subjected to the Agency's peer and administrative review and has been approved for external publication. Any opinions expressed in this paper are those of the author (s) and do not necessarily reflect the views of the Agency, therefore, no official endorsement should be inferred. Any mention of trade names or commercial products does not constitute endorsement or recommendation for use.*




- Apparent slight negative relationship between influent Mn concentration and Mn oxidases concentrations
  - Importance of abiotic removal mechanisms



# Site 1: Metals Removal

- Filter important for meeting treatment goals
- Arsenic
  - Oxidation + Fe particle removal
  - < MCL in filter effluent
  - 1-2-week acclimation time
- Iron
  - Oxidation + particle removal
  - 1-week acclimation time
- Manganese
  - Oxidation + surface coating
  - Improved in all 3 columns
  - 5-month acclimation time



# Additional Pilot Contactors for Comparisons

Contactor	Media	EBCT (min)	NH <sub>3</sub> [mg N/L] (% Removal)	Fe [mg/L] (% Removal)	Mn [µg/L] (% Removal)	As [µg/L] (% Removal)
1a	12 mm Gravel	9 ± 2	3.5 ± 0.4 (93%)	3.3 ± 0.9 (48%)	20 ± 4 (40%)	20 ± 9 (34%)
1b	2.2 mm Ceramic	16 ± 6	3.5 ± 0.4 (68%)	3.3 ± 0.9 (63%)	20 ± 4 (21%)	20 ± 9 (38%)
2	2.2 mm GAC	16	2.1 (59%)	3.1 (22%)	196 (53%)	< 2
3	2.0 mm Ceramic	16	3.1 (100%)	0.1 (23%)	57 (92%)	< 2
4	1.6 mm Ceramic	25	3.1 (100%)	1.1 (-41%)	52 (28%)	23 (-24%)
5	1.6 mm Ceramic	25	2.1 (85%)	2.1 (62%)	22 (-5%)	< 2

All systems dosed orthophosphate